

## OKK HM SERIES OIL/AIR REQUIREMENTS

### OIL REQUIREMENTS:

<u>LUBE AREA</u>	<u>OIL TYPE</u>	<u>HM-X6000</u>
SPINDLE HEAD OIL/AIR MIST	MOBILE DTE LIGHT 12K RPM	.52 Gal.
SPINDLE HEAD COOLER UNIT	MOBILE VELOCITE #3	19 Gal.
WAYS	MOBILUX EP 2	2000 HRS
OIL FOR AIR	MOBILE DTE LIGHT	6 OZ.
HYDRAULIC	MOBILE DTE LIGHT	5.2 Gal.
MAGAZINE	SHELL TONNA V68	.26 Gal.
COOLANT		104 Gal.

### AIR REQUIREMENTS:

MIN 18CFM @ 70-100 PSI

AIR FITTING SIZE: 5/8 DIA. MINIMUM ID

Revised 10/16/09

## OKK HM SERIES POWER REQUIREMENTS

<u>MODEL</u>	<u>H.P</u>	<u>KVA</u>	<u>AMPS @ 220</u>	<u>AMPS @ 480</u>
HM-X6000 (12,000 RPM)		76	199	91

CLASS 3 GROUNDING LESS THAN 100 OHMS REQUIRED

Revised 10/16/09