

## OKK KCV SERIES POWER REQUIREMENTS

<u>MODEL</u>	<u>SPECS</u>	<u>CONTROL</u>	<u>KVA</u>	<u>AMPS @ 220</u>	<u>AMPS @ 480</u>
KCV 1000-35L (12k RPM)	40 H.P.	FANUC	65	171	78
		MIT	79	207	95

**CLASS 3 GROUNDING LESS THAN 100 OHMS REQUIRED**

### AIR REQUIREMENTS:

**PRESSURE:** 70 - 100 PSI  
**FLOW:** 14CFM  
**AIR FITTING SIZE:** 5/8 DIA. MINIMUM ID

## OKK KCV SERIES OIL/AIR REQUIREMENTS

### OIL REQUIREMENTS:

<u>LUBE AREA</u>	<u>OIL TYPE</u>	<u>QUANTITY USED</u>
		<u>KCV 1000 35L</u>
SPINDLE HEAD OIL/AIR MIST	DTE LIGHT	.5 Gal.
SPINDLE HEAD COOLER UNIT	VELOCITE #3	13 Gal.
WAYS	SHELL TONNA V68	1.5 Gal.
OIL FOR AIR	DTE LIGHT	.02 Gal.
COOLANT		185 Gal.

**\*\*\*ABOVE OIL TYPES ARE MOBIL BRAND OILS UNLESS NOTED**

### AIR REQUIREMENTS:

**PRESSURE:** 70 - 100 PSI  
**AIR FITTING SIZE:** 5/8 DIA. MINIMUM ID