

## OKK KCV 1000-5AX POWER REQUIREMENTS

<u>MODEL</u>	<u>SPECS</u>	<u>CONTROL</u>	<u>KVA</u>	<u>AMPS @ 220</u>	<u>AMPS @ 480</u>
<u>KCV 1000-5AX</u>	12K	FANUC	107	281	129

**CLASS D GROUNDING LESS THAN 100 OHMS REQUIRED**

## OKK KCV 1000-5AX OIL, AIR REQUIREMENTS

### OIL REQUIREMENTS:

<u>LUBE AREA</u>	<u>OIL TYPE</u>	<u>QUANTITY USED</u>
		<u>KCV 1000-5AX</u>
Spindle Head Cooler Unit	Mobil Velocite #3	13 Gallons
Ways	Shell Tonna V68	1.6 Gallons
Hydraulic Unit	Mobil DTE Light	.6 Gallons
High Speed Lubrication Unit	Mobil DTE Light	Machine Comes Pre-Filled (Reservoir Capacity .5 Gallons)
Oil for Air	Mobil DTE Light	.03 Gallon
Coolant Tank		284 Gallons
ATC Unit	Mobilux EP2 grease	
4th & 5th Axis	Shell Albania EP grease R000	

### AIR REQUIREMENTS:

**14 CFM @ 70 - 100 PSI**

**AIR FITTING SIZE: 5/8 DIA. MINIMUM ID**