

KTM12/16F Requirements

POWER REQUIREMENTS

POWER : 200/220 VOLTS +/- 10% 3 PHASE 60HZ

CLASS 3 GROUNDING LESS THAN 100 OHMS REQUIRED

<u>MODEL</u>	<u>KVA</u>	<u>AMPS @ 220</u>
--------------	------------	-------------------

KTM12/16F	75	196
-----------	----	-----

AIR REQUIRED

80-100 PSI

17CFM

OIL REQUIREMENTS

OIL REQUIREMENTS:

KTM 12/16F

<u>LUBE AREA</u>	<u>OIL TYPE</u>	<u>QUANTITY USED</u>	<u>Interval</u>
slide ways	Mobil Vactra #2 Shell Tonna T68	1 gal.	check every 8 hrs.
Oil Cooler	Mobil Velocite #6 Shell Tellus 10	51 gal.	replace @ 1000/hrs
Hydraulic Unit	Mobil DTE Light Shell Tellus 32	69 gal.	replace @ 1000/hrs
oil mist lubricator	Mobil Velocite #6 Shell Tellus 10	.3 gal.	check every 8 hrs.
air / oil lubricator	Mobil DTE Light Shell Tellus 32	8oz.	check every 8 hrs.
coolant		185 gal.	check every 8 hrs.