

OKK MCV SERIES POWER REQUIREMENTS

<u>MCV 1260</u>	35 H.P				
		FANUC	55	144	66
		MITA	66	173	79
	40 H.P. / 13 K RPM	FANUC	60	157	72
		MITA	70	183	84

CLASS 3 GROUNDING LESS THAN 100 OHMS REQUIRED

OIL REQUIREMENTS:

<u>LUBE AREA</u>	<u>OIL TYPE</u>	<u>Quantity</u>
		<u>MCV 1260</u>
SPINDLE HEAD OIL/AIR MIST	MOBIL DTE LIGHT (8,000 RPM & ABOVE)	1.1 GAL.
SPINDLE HEAD COOLER UNIT	MOBIL VELOCITE #6	17 GAL.
WAYS	SHELL TONNA V68	1.5 GAL.
OIL FOR AIR	MOBIL DTE LIGHT	6 OZ.
COOLANT		159 GAL.
WAY LUBE AIR SYSTEM	SHELL TONNA V68	6 OZ.

AIR REQUIREMENTS:

**UP TO 8K RPM MIN 8 CFM @ 70-100 PSI
8K RPM AND ABOVE MIN 14 CFM @ 70-100 PSI**

AIR FITTING SIZE: 5/8 DIA. MINIMUM ID