

# SL45/2200 Power, Air, Oil Requirements

## Power

POWER : 200/220 VOLTS +/- 10% 3 PHASE 60HZ

CLASS 3 GROUNDING LESS THAN 100 OHMS REQUIRED

| <u>MODEL</u> | <u>KVA</u> | <u>AMPS @ 220</u> |
|--------------|------------|-------------------|
| SL45/2200    | 68         | 179               |

## Air

|                          |                        |
|--------------------------|------------------------|
| <b>AIR REQUIREMENTS:</b> | <b>80-100 PSI 8CFM</b> |
|--------------------------|------------------------|

## Oil

| <u>LUBE AREA</u> | <u>OIL TYPE</u>                    |           | <u>QUANTITY USED</u> | <u>Interval</u>                           |
|------------------|------------------------------------|-----------|----------------------|---|
| Chuck            | Mobil XHP222 Special               |           | .2 OZ                | grease daily                              |
| slide ways       | Shell Oil T68                      |           | .53 Gal.             | check daily                               |
|                  | Mobil Vactra #2                    |           |                      | change filter every 2000hrs               |
| coolant          | your choice (avoid full synthetic) | SL45/2200 | 47.5 Gal.            | check daily                               |
| Hydraulic Unit   | Mobil DTE 24                       |           | 3.7 Gal.             | check level daily<br>change every 2000hrs |