

OKK VG5000 SERIES POWER REQUIREMENTS

<u>MODEL</u>	<u>SPECS</u>	<u>CONTROL</u>	<u>KVA</u>	<u>AMPS @ 220</u>	<u>AMPS @ 480</u>
VG5000 (12k RPM)	40 H.P.	FANUC	70	184	84

CLASS 3 GROUNDING LESS THAN 100 OHMS REQUIRED

AIR REQUIREMENTS:

PRESSURE: 70 - 100 PSI
FLOW: 17CFM
AIR FITTING SIZE: 5/8 DIA. MINIMUM ID

OKK VG5000 SERIES OIL/AIR REQUIREMENTS

OIL REQUIREMENTS:

<u>LUBE AREA</u>	<u>OIL TYPE</u>	<u>QUANTITY USED</u>
		<u>VG5000</u>
SPINDLE HEAD OIL/AIR MIST	DTE LIGHT	.5 Gal.
SPINDLE HEAD COOLER UNIT	VELOCITE #3	19 Gal.
WAYS	MOBILITH AW0	.10 Gal.
OIL FOR AIR	DTE LIGHT	.02 Gal.
COOLANT		100 Gal.
MAGAZINE LUBE	SHELL TONNA V68	.20 Gal.
HYDRAULIC	DTE LIGHT	5.2 Gal.
TABLE LUBE	MOBIL GEAR 629	2.1 Gal.

***ABOVE OIL TYPES ARE MOBIL BRAND OILS UNLESS NOTED